

P.O. Box: 48577, DUBAL, U.A.E. Tel: 04 267 8866, Fax: 04 267 8855 P.O. Box: 457, SHARJAH, U.A.E.

ص.ب: ٤٨٥٧٧، **دېي**، إ.ع.م. هاتف ٢٦٨ ٧٢٦ ٤ - فاكس: ٥٥٨٨ ٧٢٦ ٤ -صي: ٤٥٧، الشارقة، إ.ع.م. مانف ۲۰۱۸ م ده ۲ د ناکس ۲۰۱۹ ۱۳۵۰ Tel: 06 565 8866, Fax: 06 565 6699



E-mail: info@zulekhahospitals.com • Website: www.zulekhahospitals.com

USAGE INSTRUCTIONS, CARE AND MAINTENANCE OF BRAUN THERMOSCANS

- To achieve accurate readings, make sure a new clean probe cover is in place before each measurement
- When the probe cover is in place, the unit turns on automatically. Wait for the ready signal to beep
- Fit the probe snuggly into the ear canal, then push the start button, The unit will beep once. The green ExacTemp light above the start button will start flashing indicating correct probe placement and an accurate reading being taken.
- A long beep and solid green ExacTemp light signals the end of the measurement.
- If the probe is not placed in stable position during measurement, the device beeps and the green ExacTemp light goes out and the unit will give a POS (position error).
- If the patient has hearing aid, remove the same and wait for 20 minutes before taking the measurement.
- Never use the thermoscan without the probe covers installed.
- Damaged, perforated or soiled probe covers should not be used.
- Ensure that the probe window is clean dry and undamaged before each use.
- If the probe window is soiled with ear wax (possible only if the probe covers are not used), dust or finger prints, gently wipe its surface with a cotton swab slightly moistened with alcohol and immediately wipe dry with a clean cotton swab. After cleaning allow at least 5 minutes drying time before taking measurements.
- If the probe window is damaged, send the thermometer to biomedical department for confirmation. Once the damage is confirmed return the same to the store department.